23/06/2023

TECHNICAL DATASHEET

Code	T50T-M31-PP
Brief Description	Adhesive tape in Polypropylene, Hot Melt, transparent, mm 50x66 m
Color	Transparent
Country of origin	Italy
BOPP thickness	28 micron
Total thickness	48 micron
Adhesiveness on steel	10 N/25 mm (PSTC 101)
Load at break	120 N/25 mm (PSTC 131)
Stretching at break	145% (PSTC 131)
Temperature resistance	60°C
Adhesive type	Synthetic rubber hot melt
Dimensions outer	66 m x 50 mm
Package	Box of 36 pieces

Description

PPL adhesive tape with synthetic rubber-based adhesive (Hot Melt) is ideal to close cardboard packaging and it is the best solution in terms of price and quality.
This type of PPL adhesive tape is not affected by temperature changes, humidity, stress and has excellent resistance to aging and UV rays exposure.
PPL adhesive tape is suitable for all purposes and all surfaces.

SERPAC s.r.l. Via Campania, 4/6 20054 Segrate (MI)
dati fiscali P. IVA. 05083510965 cap. soc. € 20.000,00
reg. imprese Registro di Milano R.E.A.1795952
fatturazione cod. SDI. M5UXCR1 serpacsrl@lamiapec.it
contatti tel. (+39) 02 218 71 585 fax (+39) 02 269 52 031
web www.serpac.it info@serpac.it
azienda certificata UNI EN ISO 9001:2015 CERTIQUALITY n. 17284