

# TECHNICAL DATASHEET

<b>Code</b>	4G-3516-60AL
<b>Brief Description</b>	UN 4G box PG516 + aluminium bottle of 6,25 L each
<b>Type</b>	PG516
<b>Print</b>	Neutral
<b>Provided</b>	Flat with 1 bottle of 6,250 L each
<b>Approval</b>	4G/Y8.6/S/** B/SERPAC.412-170054
<b>Country of origin</b>	Italy
<b>Vibration test</b>	Yes (178.608 - 49CFR)
<b>Dimensions inner</b>	195 x 195 x 360 h mm
<b>Dimensions outer</b>	200 x 200 x 380 h mm
<b>Weight of the fibreboard box</b>	0,410 kg each


**For shipping:**

✓ ADR ✓ RID ✓ ADN ✓ IMDG ✓ IATA

Approved for	Max gross weight packaging kg	Certification / (Extension)	Tape, width, system
Nr. 1 aluminium bottle of 6,25 L each	8,60 (Y8.60)	PG516-4G/Y8.6	—
Nr. 1 aluminium bottle of 6,25 L each	12,60 (Z12.60)	PG516-4G/Z9.8	—

**Description**
**UN certified 4G fibreboard boxes supplied with 1 aluminum bottle of 6,250 L - PG616.**

UN certified 4G boxes are supplied with the specific inner packagings (HDPE bags) with which they have been tested.

Ideal for shipping samples, for example of chemical products or for the supply of the product.

The 4G boxes supplied with the specific inner packaging do not require the use of vermiculite.

Innovative and easy to use solution, it guarantees time savings in preparation, shipping security and lower transport costs.

The 4G boxes supplied with glass bottles are approved for the shipment of dangerous goods according to ADR, RID, ADN, IMDG and ICAO-TI / IATA.

They can be used to ship goods belonging to packing groups II (Y) and III (Z).