

TECHNICAL DATASHEET

| | |
|-------------------------------------|--|
| Code | 4G-3982-50PE |
| Brief Description | UN 4G box PG982 + HDPE plastic jerrycan of 5,0 L |
| Type | PG982 |
| Print | Neutral |
| Provided | Flat with 1 jerrycan of 5 L each |
| Approval | 4G/Y7/S/**/B/SERPAC.412-110271 |
| Country of origin | Italy |
| Vibration test | Yes (178.608 - 49CFR) |
| Dimensions inner | 182 x 182 x 251 h mm |
| Dimensions outer | 190 x 190 x 270 h mm |
| Weight of the fibreboard box | 0,232 kg each |


For shipping:

✓ ADR ✓ RID ✓ ADN ✓ IMDG ✓ IATA

| Approved for | Max gross weight packaging kg | Certification / (Extension) | Tape, width, system |
|----------------------------|-------------------------------|-----------------------------|---|
| Nr. 1 HDPE jerrycan of 5 L | 7 (Y7) | PG982-4G/Y7 | PP36 , 50 mm, U |

Description
UN certified 4G fibreboard boxes supplied with 1 HDPE jerrycan of 5 L - PG982.

UN certified 4G boxes are supplied with the specific inner packagings (HDPE bags) with which they have been tested.

Ideal for shipping samples, for example of chemical products or for the supply of the product.

The 4G boxes supplied with the specific inner packaging do not require the use of vermiculite.

Innovative and easy to use solution, it guarantees time savings in preparation, shipping security and lower transport costs.

The 4G boxes supplied with glass bottles are approved for the shipment of dangerous goods according to ADR, RID, ADN, IMDG and ICAO-TI / IATA.

They can be used to ship goods belonging to packing groups I (X), II (Y) and III (Z).

Attention:

1 – Before inserting any liquid, it is necessary to verify the chemical compatibility between the packagings and the dangerous goods that you want to insert;

2 – For the manual closure of the tanks, it is necessary to use the torque wrench (sold separately).