



TECHNICAL DATASHEET

Code	4G-3516-60AL
Brief Description	UN 4G box PG516 + aluminium bottle of 6,25 L each
Type	PG516
Print	Neutral
Provided	Flat with 1 bottle of 6,250 L each
Approval	4G/Y8.6/S/** B/SERPAC.412-170054
Country of origin	Italy
Vibration test	Yes (178.608 - 49CFR)
Dimensions inner	195x195x360h mm
Dimensions outer	200x200x380h mm
Weight of the fibreboard box	0,410 kg each

**For shipping:**

✓ ADR ✓ RID ✓ ADN ✓ IMDG ✓ IATA

Approved for	Max gross weight packaging kg	Certification / (Extension)	Tape, width, system
Nr. 1 aluminium bottle of 6,25 L each	8,60 (Y8.60)	PG516-4G/Y8.6	—
Nr. 1 aluminium bottle of 6,25 L each	12,60 (Z12.60)	PG516-4G/Z9.8	—

Description**UN certified 4G fibreboard boxes supplied with 1 aluminum bottle of 6,250 L - PG616.**

UN certified 4G boxes are supplied with the specific inner packagings (HDPE bags) with which they have been tested. Ideal for shipping samples, for example of chemical products or for the supply of the product. The 4G boxes supplied with the specific inner packaging do not require the use of vermiculite. Innovative and easy to use solution, it guarantees time savings in preparation, shipping security and lower transport costs. The 4G boxes supplied with glass bottles are approved for the shipment of dangerous goods according to ADR, RID, ADN, IMDG and ICAO-TI / IATA. They can be used to ship goods belonging to packing groups II (Y) and III (Z).