













09/02/2024

TECHNICAL DATASHEET

Code	4G-3143-NT	
Brief Description	UN 4G box PG843/NT, mm 390x305x140h inner useful	
Туре	PG843	
Print	Neutral	
Provided	Flat	
Approval	4G/Y4/S/** B/SERPAC.412-070086	
Country of origin	Italy	
Vibration test	Yes (178.608 - 49CFR)	
Dimensions inner	390x305x140h mm	(D)
Dimensions outer	400x315x155h mm	
Dimensions package	720x480x200h mm	For shipping:
Dimensions pallet	1200x1000x1400h mm	→ ADR → RID → ADN → IMDG → IATA
Weight of the fibreboard box	0,317 kg each	
Package	Pack of 14 pieces	

Approved for	Max gross weight packaging kg	Certification / (Extension)	Tape, width, system
UN3316 Chemical kit - 4 packagings Spectroquant	4 (Y4)	PG843-4G/Y4	<u>PP36</u> , 50 mm <u>, U</u>

Description

A fibreboard 4G box, referred to in regulations as "UN-certified 4G fibreboard box", is a specific type of fibreboard UN-certified outer packaging containing one or more specific inner packaging(s). In order to respect their certification validity, UN-certified 4GV boxes must be used only together with the specific inner packaging and content they were tested with and approved by the certifying body. This specific inner packaging will be the same mentioned in the test report. Furthermore, maximum gross weight and closing instructions defined in the test report must be observed, too (dimension of adhesive tape, type of adhesive tape and closing system). Any unauthorized change would invalidate the certification. To check details of UN certification you can read the "Technical details" of 4G box or the test report of the UN-certified 4G packaging.

Our 4G boxes are certified according to ADR, RID, ADN, IMDG and ICAO-TI / IATA regulations, shippers are responsible of checking if their dangerous goods can be shipped with the chosen transport mode.