

TECHNICAL DATASHEET

| | |
|-------------------------------------|--|
| Code | 4GV-80A-NT |
| Brief Description | UN 4GV box PGV80 assembled + Vermiculite, mm 100x100x245h inner useful |
| Type | PGV80 |
| Print | Neutral |
| Provided | Assembled - 1 extra bag - with vermiculite |
| Approval | 4GV/X2.75/S/** B/SERPAC.412-090136 |
| Country of origin | Italy |
| Dimensions inner | 140x140x285h mm |
| Dimensions outer | 150x150x305h mm |
| Dimensions pallet | 1200x800x1750h mm |
| Weight of the fibreboard box | 0,200 kg each |


For shipping:

✓ ADR ✓ RID ✓ ADN ✓ IMDG ✓ IATA

| Approved for | Max gross weight inner packaging kg | Max gross weight packaging kg | Certification / (Extension) | Minimum distance of Vermiculite between containers, bottom and lid walls mm | Tape, width, system |
|---|-------------------------------------|-------------------------------|-----------------------------|---|---------------------|
| Objects and inner packagings of all types | 1,75 | 2,75 (X2.75) | PGV80-4GV/X2.75 | 20 | — |
| Lithium Battery with Vermiculite (P908, P909, P910) | 1,75 | 2,75 (X2.75) | | Da verificare* | — |

Description
UN certified 4GV fibreboard, assembled supplied, with 1 PE bag - PGV80.

UN certified 4GV packagings (UN certified 4GV fibreboard boxes) suitable for shipping objects or any kind of inner packagings containing solid or liquid substances of packing group I, II, III.

For a proper use of UN certified 4GV boxes, it is important to follow the instructions printed on the flap of each box.

The correct preparation of these UN certified 4GV boxes requires their use in combination with vermiculite (inert absorbent material).