

## TECHNICAL DATASHEET

<b>Code</b>	4GV-81A-NT
<b>Brief Description</b>	UN 4GV box PGV81 assembled + Vermiculite, mm 150x150x315h inner useful
<b>Type</b>	PGV81
<b>Print</b>	Neutral
<b>Provided</b>	Assembled - 1 extra bag - with vermiculite
<b>Approval</b>	4GV/X4/S/** B/SERPAC.412-060035
<b>Country of origin</b>	Italy
<b>Dimensions inner</b>	190x190x355h mm
<b>Dimensions outer</b>	200x200x380h mm
<b>Dimensions pallet</b>	1200x800x1800h mm
<b>Weight of the fibreboard box</b>	0,410 kg each


**For shipping:**

✓ ADR ✓ RID ✓ ADN ✓ IMDG ✓ IATA

Approved for	Max gross weight inner packaging kg	Max gross weight packaging kg	Certification / (Extension)	Minimum distance of Vermiculite between containers, bottom and lid walls mm	Tape, width, system
Objects and inner packagings of all types	2,40	4 (X4)	PGV81-4GV/X4	20	—
Lithium Battery with Vermiculite (P908, P909, P910)	2,40	4 (X4)		Da verificare*	—

**Description**

**UN certified 4GV fibreboard, assembled supplied, with 1 PE bag - PGV81.**

UN certified 4GV packagings (UN certified 4GV fibreboard boxes) suitable for shipping objects or any kind of inner packagings containing solid or liquid substances of packing group I, II, III.

For a proper use of UN certified 4GV boxes, it is important to follow the instructions printed on the flap of each box.

The correct preparation of these UN certified 4GV boxes requires their use in combination with vermiculite (inert absorbent material).