

## TECHNICAL DATASHEET

<b>Code</b>	4GV-81S-NT
<b>Brief Description</b>	UN 4GV box PGV81 flat + 2 bags, mm 190x190x355h inner
<b>Type</b>	PGV81
<b>Print</b>	Neutral
<b>Provided</b>	Flat - with 2 bags - without vermiculite
<b>Approval</b>	4GV/X4/S/** B/SERPAC.412-060035
<b>Box type</b>	Die-cut box
<b>Country of origin</b>	Italy
<b>Dimensions inner</b>	190x190x355h mm
<b>Dimensions outer</b>	200x200x380h mm
<b>Dimensions package</b>	840x400x130h mm
<b>Dimensions pallet</b>	1250x900x1100h mm
<b>Weight of the fibreboard box</b>	0,410 kg each
<b>Package</b>	Pack of 20 pieces



### For shipping:

✓ ADR    ✓ RID    ✓ ADN    ✓ IMDG    ✓ IATA

Approved for	Max gross weight inner packaging kg	Max gross weight packaging kg	Certification / (Extension)	Minimum distance of Vermiculite between containers, bottom and lid walls mm	Tape, width, system
Objects and inner packagings of all types	2,40	4 (X4)	PGV81-4GV/X4	20	—
Lithium Battery with Vermiculite (P908, P909, P910)	2,40	4 (X4)	PGV81-4GV/X4	Da verificare*	—

### Description

#### UN certified 4GV fibreboard, flat supplied, with PE bags - PGV81.

UN certified 4GV packagings (UN certified 4GV fibreboard boxes) suitable for shipping objects or any kind of inner packagings containing solid or liquid substances of packing group I, II, III.

UN certified 4GV boxes flat are supplied with 2 PE bags, except for PGV85 box which is supplied with only 1 PE bag.

For a proper use of UN certified 4GV boxes, it is important to follow the instructions printed on the flap of each box.

The correct preparation of these UN certified 4GV boxes requires their use in combination with vermiculite (inert absorbent material).