

TECHNICAL DATASHEET

Code	4GV-85S-NT
Brief Description	UN 4GV box PGV85 flat + bag, mm 775x575x502h inner
Type	PGV85
Print	Neutral
Provided	Flat - with 1 bag - without vermiculite
Approval	4GV/X78/S/** B/SERPAC.412-060146
Box type	Die-cut box
Country of origin	Italy
Vibration test	Yes (178.608 - 49CFR)
Dimensions inner	775x575x502h mm
Dimensions outer	800x600x550h mm
Dimensions package	1400x950x310h mm
Dimensions pallet	1400x1000x1450h mm
Weight of the fibreboard box	4,700 kg each
Package	Pack of 9 pieces



For shipping:

✓ ADR ✓ RID ✓ ADN ✓ IMDG ✓ IATA

Approved for	Max gross weight inner packaging kg	Max gross weight packaging kg	Certification / (Extension)	Minimum distance of Vermiculite between containers, bottom and lid walls mm	Tape, width, system
Objects and inner packagings of all types	45,00	78 (X78)	PGV85-4GV/X78	60	RB , 50 mm, U
Lithium Battery with Vermiculite (P908, P909, P910)	45,00	78 (X78)	PGV85-4GV/X78	Da verificare*	RB , 50 mm, U
Nr. 1 Lithium Battery with Grain (P908, P909, P910)	68,00	110 (110)	PG2024	Da verificare*	RB , 50 mm, U

Description

UN certified 4GV fibreboard, flat supplied, with PE bags - PGV85.

UN certified 4GV packagings (UN certified 4GV fibreboard boxes) suitable for shipping objects or any kind of inner packagings containing solid or liquid substances of packing group I, II, III.

UN certified 4GV boxes flat are supplied with 1 PE bag.

For a proper use of UN certified 4GV boxes, it is important to follow the instructions printed on the flap of each box.

The correct preparation of these UN certified 4GV boxes requires their use in combination with vermiculite (inert absorbent material)